


Product Applications	Target Customers	Range USP
<ul style="list-style-type: none"> Suitable for most Industrial and Commercial Applications Dockyards and ship building Power stations Factories Construction Forges & Mining Processing plants Military Installations Warehouses Marquees & Events Exhibition halls Hospitals Temporary Buildings 	<ul style="list-style-type: none"> Hire Companies Construction Firms Procurement Managers Facility Management Wholesalers & Resellers Large Industrial Units 	<ul style="list-style-type: none"> The industry standard Fireflo range of portable infra red space heaters and fan heaters is a fixture in many of the worlds leading hire fleets and industrial supply catalogues. Designed using the very latest in heating and airflow technology the range includes infra red heaters, standard fan heaters and high volume machines suitable for ducting through multiple outlets or long distances. All built to withstand industrial use using the same high spec of materials and production methods this extensive range has something to suit every application and is an ideal safe, clean, fume free alternative to gas and diesel. The Super Industrial Range offers some phenomenal statistics – upto 125kW of heat, 100°C (heat rise) in a single pass, 5000pa of pressure, 10,000m³/hr and can be ducted over 100m - and is perfectly comfortable providing heat in place of, or in addition to an existing heating system. The standard multi-stage controls can be adapted to suit most requirements so that constant airflow and temperatures are maintained.

Product Image	Product Specs	Product USP
<p>FF42</p> 	<p>Airflow Rate 4000m³/hr Nominal Output 42kW Supply 400v 50hz Plug Size 63A Sound (3m) 73dB(A) Spigot 500mm Mobility Portable Thermostat Standard Remote Thermostat Standard Max Ducting 30m Dimensions HxWxD (mm) 1000x700x1100 Weight 130kG Overtmp protection Yes Phase protection Yes 24v Control Circuit</p>	<p>The most powerful 63A heater available. Designed and built for industrial use the FF42 features variable heat output, 24V control circuit for safety, remote thermostat socket, spigot, over temperature protection and an auto run on as standard. The FF42 is fitted with a powerful forward curved impeller that can deliver heat along 30m of ducting</p>

Off-Fan-21kW-42kW settings



Thermostat Thermostat coupler


Lifting eyes for maximum portability

Both Industrial & Super Industrial Heaters are ductable...



...with a series of spigot options available



<p>FF63</p> 	<p>Airflow Rate 8000m³/hr Nominal Output 63kW Fan Type Contra bladed Supply 400v 50hz Plug Size 125A Sound (3m) 75dB(A) Spigot 500mm Mobility Portable Thermostat Standard Dimensions HxWxD (mm) 1000x700x1690 Weight 200kG Overtmp protection Yes Phase protection Yes Max Ducting 50m</p>	<p>An 63kW heater for heavy duty applications. Ideal for use in shipping, surface coating or large scale heating applications; the FF63 features a powerful contra rotating fan motor for pumping heat down long lengths of ducting, a heavy duty build, thermostatic control, over temperature protection and lockable castors</p>
--------------------------------------------------------------------------------------------------------	--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------