


Product Applications	Target Customers	Range USP
<ul style="list-style-type: none"> <li>Suitable for most Industrial and Commercial Applications</li> <li>Dockyards and ship building</li> <li>Power stations</li> <li>Factories</li> <li>Construction</li> <li>Forges &amp; Mining</li> <li>Processing plants</li> <li>Military Installations</li> <li>Warehouses</li> <li>Marquees &amp; Events</li> <li>Exhibition halls</li> <li>Hospitals</li> <li>Temporary Buildings</li> </ul>	<ul style="list-style-type: none"> <li>Hire Companies</li> <li>Construction Firms</li> <li>Procurement Managers</li> <li>Facility Management</li> <li>Wholesalers &amp; Resellers</li> <li>Large Industrial Units</li> </ul>	<ul style="list-style-type: none"> <li>The industry standard Fireflo range of portable infra red space heaters and fan heaters is a fixture in many of the worlds leading hire fleets and industrial supply catalogues. Designed using the very latest in heating and airflow technology the range includes infra red heaters, standard fan heaters and high volume machines suitable for ducting through multiple outlets or long distances. All built to withstand industrial use using the same high spec of materials and production methods this extensive range has something to suit every application and is an ideal safe, clean, fume free alternative to gas and diesel.</li> </ul>

Product Image	Product Specs	Product USP
<p><b>FF42</b></p>  <p><b>40kW</b> Nominal Output</p>	<p><b>Airflow Rate</b> 3956m³/hr  <b>Nominal Output</b> 40kW  <b>Supply</b> 400v 50hz  <b>Plug Size</b> 63A  <b>Spigot</b> 500mm  <b>Mobility</b> Portable  <b>Thermostat</b> Standard  <b>Remote Thermostat</b> Standard  <b>Max Ducting</b> 20m  <b>Dimensions HxWxD (mm)</b> 921x571x1322  <b>Weight</b> 111kg  <b>Overtemp protection</b> Yes  <b>Phase protection</b> Yes  <b>24v Control Circuit</b>  <b>Phase Rotation Relay and Warning</b> Yes  <b>Manual Reset Overheat</b>  <b>Fail Safe</b></p>	<ul style="list-style-type: none"> <li>The most powerful 63A heater available. Designed and built for industrial use the FF42 features variable heat output, 24V control circuit for safety, remote thermostat socket, spigot, over temperature protection and an auto run on as standard.</li> <li>For added convenience, the FF42 now features a phase rotation relay that won't let the unit start unless all 3 phases are in sync, as well as a warning light on the control panel to alert the user.</li> <li>We've also added the same manual overheat reset system used on the FFHT32 and FFVH32 which shuts the unit down if necessary.</li> <li>The FF42 is fitted with a powerful forward curved impeller that can deliver heat along 20m of ducting.</li> </ul>



Easy to use controls with built in safety features as standard



Ductable to 20m in conjunction with a 500mm aluminium duct



Forklift skids and lifting eyelets



**Customer Order Line** 01527 830610  
**Technical Advice** 01527 395635  
**E:** sales@broughtoneap.co.uk  
**F:** 01527 527558

**Accounts**  
 Rookery Works, Newchapel Rd  
 Kidsgrove, Stoke on Trent  
 Staffordshire, ST7 4SF 01782 777559

**Sales & Manufacturing**  
 Units 24-25, Crossgate Road  
 Park Farm Industrial Estate  
 Redditch, B98 7SN 01527 830610