


<p>Product features</p> <ul style="list-style-type: none"> • Easy to use touch screen • Fully programmable • Full modulating operation • High quality pump • Frost protection • Overheat protection • Automatic pressure relief valve • Low & Over pressure protection • 99% efficiency • 22kW to 36kW versions available 	<p>WB Programmable Electric Boiler</p> <ul style="list-style-type: none"> • Say goodbye to daily site visits to adjust the temperatures of your boiler as it dries a screed floor. The new WB Programmable range of boilers can be pre programmed before leaving the depot to increase and decrease the water temperature as required, meaning all you have to do on site is plug it in and leave it to get on with the job. • Designed with the everyday user in mind our simple to use touch screen controller can be easily set to suit the application without the need for a PHD in programming or logic. There's also password protection as we understand what happens on site, where even the most sensible of Tradesman can be overcome by curiosity. • Once up and running the colourful LCD screen displays exactly what's happening and how far through the program it is. On top of all that there's battery backup memory that ensures the program picks up where it left off in the event of a power cut, a frost protection function, temperature probe failure warning and even a fully manual setting. As with our original WB22 these new versions have a full range of safety features for peace of mind. • 22kW to 36kW versions available 
--	--

<p>Product Image</p>  <p>22 & 36kW Versions</p> <p>Fully programmable digital controller</p>	<p>WB22/20 Specifications</p> <ul style="list-style-type: none"> • Flow Rate 2.7 - 3.5m³/hr • Supply 400v 50hz • Water Temperature Range 20°C to 80°C • Fully Portable • Power 22kW • Plug Size 32A • Dimensions HxWxD (mm) 1100x650x470 • 10 litre expansion tank included as standard. • Touch screen controller with floor drying program capability. • Over-temperature and over-pressure protection. • Relay failure protection 	<p>WB36/21 Specifications</p> <ul style="list-style-type: none"> • Commercial circulation pump with water flows of up to 7m³/h. (This is larger than the standard pump). • Supply- 3P+N+E 63A 50Hz. • 36kW machine that draws 54A. • Fully Portable • Dimensions HxWxD (mm) 1122x650x650 • 10 litre expansion tank included as standard. • Touch screen controller with floor drying program capability. • Over-temperature and over-pressure protection. • Water temperature from 5-80 degrees.
---	---	---